Intrinsically Safe - Dust
LIPS® SERIES E101

Part Number Coding

E101	Travel	A	Y	Conn / Cable	Option 1	Option 2	Option 3	Option 4	Z code

Stand Alone Linear Position Sensor

Travel

mm of stroke	Value

Electrical Interface Options

Input	Output	
+ 5 V dc	See below	A

Calibration Adjusters — Standard Fit

Sealed Trim Pots	Y

Connector / Cable

Cable - Radial Gland IP67	Please specify cable length in cm.	Ixx	eg. L2000 specifies 20 metres of cable with an axial cable gland
Connector - Axial IP67		J	
Connector - Radial IP67/68		K	
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx	

OPTIONS

Body Fittings — Option 1

M5 Rod Eye on Body	Only available with options K & I	N
Body Clamps (1 pair)		P
Body Clamps (2 pairs)		P2

Spring Return — Up to 250mm stroke only — Option 2

Spring return to **extended** position	R
Spring return to **retracted** position	S

Push Rod End Fitting — Option 3

None - M5 female thread only	Standard option no code	Blank
Domed End (for use with option R)		T
M5 Rod Eye on Push Rod		U

Non Captive Target Tube — Option 4

Target tube not retained in body	V

Calibration (output from galvanic barrier)

0.5 to 9.5 volts	Z010
4 to 20 mA	Z420