

Intrinsically Safe - Dust LIPS® SERIES E111		Part Number Coding										
		E111	Travel	A	Y	Conn / Cable	N/Blank	Option 1	Option 2	Option 3	Option 4	Z code
Stand Alone Linear Position Sensor												
Travel												
mm of stroke	Value											
Electrical Interface Options												
Input	Output											
+ 5 V dc	See below	A										
Calibration Adjusters												
Scaled Trim Pots	Y											
Connector / Cable												
Cable - Radial Gland IP67	Please specify cable length in cm.	Ixx										
Connector - Axial IP67		J										
Connector - Radial IP67		K										
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx										
		eg. L2000 specifies 20 metres of cable with an axial cable gland										
Rod End on Body												
Radial (options K or I)	Must be fitted	N										
Axial (options J or L)	Not available	Blank										
OPTIONS												
Body Fittings												
Body Clamps (1 pair)	P											
Body Clamps (2 pairs)	P2											
Spring Return												
Up to 250mm stroke only												
Spring return to extended position	R											
Spring return to retracted position	S											
Push Rod Fitting												
None - M8 female thread only	Standard option no code	Blank										
M8 Dome End on Push Rod		U										
Non Captive Push Rod												
Push rod not retained in body	V											
Calibration (output from galvanic barrier)												
0.5 to 9.5 volts	Z010											
4 to 20 mA	Z420											