

Part Number Coding

LIPS® SERIES P101			P101	Travel	Electrical Interface	Sealed Adjuster	Conn / Cable and	Option 1	Option 2	Option 3	Option 4
Stand Alone Linear Position Sensor											
Travel											
mm of stroke	Value										
Electrical Interface Options											
Input	Output										
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric		A								
24V dc nom. +9-28V	0.5-4.5V dc		G								
±15V dc nom. ±9-28V	±5V dc		B								
24V dc nom. +13-28V	0.5 to 9.5V dc		C								
± 15V dc nom. ±13.5-28V	±10 V dc		D								
24V dc nom. +18-28V	4 to 20mA (2 wire)		E								
24V dc nom. +13-28V	4 to 20mA (3 wire sink)		F								
24V dc nom. +13-28V	4 to 20mA (3 wire source)		H								
Calibration Adjusters - Axial (options J, L or M) only											
Trim Pots Accessible	Blank										
Sealed Trim Pots	Y										
Connector / Cable											
Cable - Radial Gland IP67	Please specify cable length in cm.	Ixx	Trim Pots not accessible except with Z170 option								
Connector - Axial IP65	Hirschmann GD series	J									
Connector - Radial IP67	Hirschmann M12	K	Trim Pots not accessible except with Z165 option								
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland								
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx	Note: restricted cable pull strength								
OPTIONS											
Body Fittings			Option 1								
M5 Rod Eye on Body	Only available with options K &	N									
Body Clamps (1 pair)		P									
Body Clamps (2 pairs)		P2									
Spring Return			Option 2								
Up to 250mm stroke only											
Spring return to extended position		R									
Spring return to retracted position		S									
Push Rod End Fitting			Option 3								
None - M5 female thread on!	Standard option no code	Blank									
Dome End (for use with option R)		T									
M5 Rod Eye on Push Rod		U									
Non Captive Push Rod Tube			Option 4								
Push Rod not retained in body		V									