

			Part Number Coding									
LIPS® SERIES P103			P103	Travel	Electrical Interface	Sealed Adjusters	Conn / Cable	Option 1	Option 2	Option 3	Option 4	Option 5
Short Stroke Position Sensor												
Travel												
mm of stroke		Value										
Electrical Interface Options												
Input	Output											
+ 5V dc nom. ± 0.5V	0.5 to 4.5V dc ratiometric	A										
24V dc nom. +9-28V	0.5-4.5V dc	G										
±15V dc nom. ±9-28V	±5V dc	B										
24V dc nom. +13-28V	0.5 to 9.5V dc	C										
± 15V dc nom. ±13-28V	±10 V dc	D										
24V dc nom. +18-28V	4 to 20mA (2 wire)	E										
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F										
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H										
Calibration Adjusters												
Trim Pots Accessible		Blank										
Sealed Trim Pots		Y										
Connector / Cable												
Connector - Axial IP65	Hirschmann GD series	J										
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx										
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx										
OPTIONS												
Housing												
Front Flange		N										
Body Clamp												
Body Clamps (1 pair)		P										
Spring Return												
Spring Return		R										
Plunger End Fitting												
Dome End		T										
Plunger (Armature) Guide												
Free Plunger (no inner guide bearing)	Not available with option R or T	V										