

			Part Number Coding									
CYLINDER LIPS® P106			P106	Travel	Electrical Interface	Sealed Adjusters	Conn / Cable	N	Option 2	R	Option 4	
Internally Mounted Cylinder Sensor												
Travel												
mm of stroke		Value										
Electrical Interface Options												
Input		Output										
+ 5V dc nom. ± 0.5V		0.5 to 4.5V dc ratiometric	A									
24V dc nom. +9-28V		0.5-4.5V dc	G									
±15V dc nom. ±9-28V		±5V dc	B									
24V dc nom. +13-28V		0.5 to 9.5V dc	C									
± 15V dc nom. ±13-28V		±10 V dc	D									
24V dc nom. +18-28V		4 to 20mA (2 wire)	E									
24V dc nom. +13-28V		4 to 20mA (3 wire sink)	F									
24V dc nom. +13-28V		4 to 20mA (3 wire source)	H									
Calibration Adjusters												
Trim Pots Accessible		Blank										
Sealed Trim Pots		Y										
Connector / Cable												
Connector - Axial IP65		Hirschmann GD series	J									
Cable - Axial Gland IP67		Please specify cable length in cm.	LXX	eg. L2000 specifies 20 metres of cable with an axial cable gland								
Cable - Axial Short Gland IP67		Please specify cable length in cm.	MXX	Note: restricted cable pull strength								
OPTIONS												
Internal Housing Size												
20 mm Diameter		Standard Fit	N									
Electronics Housing												
Flanged		T										
M18 Thread		P										
Target Tube												
Stainless Steel 7.7 mm		Standard Fit	R									
Flange Style and Position Please select one.												
None		U										
P&G		Vxx										
Tempo		Wxx										
PH		Xxx										
Please specify flange position xx from Target Tube end in mm. eg. W17.5 specifies a Tempo style flange fitted 17.5 mm from the front face												
See Drawing TG24-11 for flange details												