Part Number Coding

CYLINDER LIPS® P106	P106	Travel	Electrical Interface	Sealed Adjusters	Conn / Cable and	N	Option 1	R	Option 2

Internally Mounted Cylinder Sensor

Travel	
mm of stroke	Value

Electrical Interface Options		
Input	Output	
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A
24V dc nom. +9-28V	0.5-4.5V dc	G
±15V dc nom. ±9-28V	±5V dc	B
24V dc nom. +13-28V	0.5 to 9.5V dc	C
± 15V dc nom. ±13.5-28V	±10 V dc	D
24V dc nom. +18-28V	4 to 20mA (2 wire)	E
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H

Calibration Adjusters	
Trim Pots Accessible	Blank
Sealed Trim Pots	Y

Connector / Cable			
Connector - Axial IP65	Hirschmann GD series	J	
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx	Note: restricted cable pull strength

OPTIONS			
Internal Housing Size			**Standard Fit**
20 mm Diameter	**Standard Fit**	N	
Electronics Housing			**Option 1**
Flanged		T	
M18 Thread		P	
Target Tube			**Standard Fit**
Stainless Steel 7.7 mm	**Standard Fit**	R	
Aluminium 7.0 mm		S	
Flange Style and Position	Please select one.		**Option 2**
None		U	
P&G		Vxx	
Tempo		Wxx	
PH		Xxx	
See Drawing TG24-11 for flange details			

Please specify flange position **xx** from Target Tube end in mm.
eg. W17.5 specifies a Tempo style flange fitted 17.5 mm from the front face



www.positek.com