

Part Number Coding

CYLINDER LIPS® P106			P106	Travel	Electrical Interface	Calibration Adjusters	Conn / Cable and Length	N	Option 1	Option 2	Option 3	Z code
Internally Mounted Cylinder Sensor												
Travel												
mm of stroke	5-800 mm	Value										
Electrical Interface Options												
Input	Output											
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A										
24V dc nom. +9-28V	0.5-4.5V dc	G										
±15V dc nom. ±9-28V	±5V dc	B										
24V dc nom. +13-28V	0.5 to 9.5V dc	C										
± 15V dc nom. ±13.5-28V	±10 V dc	D										
24V dc nom. +18-28V	4 to 20mA (2 wire)	E										
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F										
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H										
Calibration Adjusters												
Trim Pots Accessible		Blank										
Sealed Trim Pots		Y										
Connector / Cable												
Connector - Axial IP65	Hirschmann GD series	J										
Connector - Axial IP67	M12 - 4 pin	J +										
(for sensors with Trim Pots sealed)		Z600										
Connector - Axial IP67	M12 - 4 pin	J +										
(for sensors with Trim Pots Accessible)		Z601										
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx										
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx										
eg. L2000 specifies 20 metres of cable with an axial cable gland												
Note: restricted cable pull strength												
OPTIONS												
Internal Housing Size												
20 mm Diameter	Standard Fit	N										
Electronics Housing												
Flanged		T										
M18 Thread		P										
Target Tube												
Stainless Steel 7.7 mm	Standard Fit	R										
Aluminium 7.0 mm		S										
Flange Style and Position												
Please select one.												
None	Please specify flange position xx from Target Tube end in mm. eg. W17.5 specifies a Tempo style flange fitted 17.5 mm from the front face	U										
P&G		Vxx										
Tempo		Wxx										
PH		Xxx										
See Drawing TG24-11 for flange details												

