

**Part Number Coding**

<b>LIPS® SERIES P117</b>			<b>P117</b>	<b>Travel</b>	<b>Electrical Interface</b>	<b>Blank</b>	<b>Body &amp; Cable</b>	<b>Option 1</b>	<b>Option 2</b>	<b>Option 3</b>	<b>Option 4</b>	<b>Z code</b>
<b>Slim-line Linear Sensor</b>												
<b>Travel</b>												
mm of stroke	5-350 mm	Value										
<b>Electrical Interface Options</b>												
Input	Output											
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A										
24V dc nom. +9-28V	0.5-4.5V dc	G										
24V dc nom. +13-28V	0.5 to 9.5V dc	C										
<b>Adjusts not available</b>												
<b>Body Style</b>												
Cable - Radial Gland	Please specify cable length in cm.	IXX										
Connector - Axial		J										
Connector - Radial		K										
Cable - Axial Gland	Please specify cable length in cm.	LXX										
<b>OPTIONS</b>												
<b>Body Fittings</b>			<b>Option 1</b>									
M5 Rod Eye fitted to body	Only available on Radial Version	N										
<b>Body Clamp</b>			<b>Option 2</b>									
Body Clamps (1 pair)		P										
<b>Push Rod Fittings</b>			<b>Option 3</b>									
M5 Rod Eye fitted to Push Rod		U										
<b>Non Captive Push Rod</b>			<b>Option 4</b>									
Push Rod not retained in body		V										
<b>Tighter Linearity</b>			<b>Zsuffix</b>									
± 0.1% Linearity	from 10mm stroke only	Z650										