

**Part Number Coding**

LIPS® SERIES P118			P118	Travel	Electrical Interface	Blank	L/J	Option 1	Option 2	Option 3	Option 4	Option 5	Z code
<b>Short Stroke Slim-Line Position Sensor</b>													
<b>Travel</b>													
mm of stroke	2-50 mm	Value											
<b>Electrical Interface Options</b>													
Input	Output												
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A											
24V dc nom. +9-28V	0.5-4.5V dc	G											
24V dc nom. +13-28V	0.5 to 9.5V dc	C											
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H											
<b>Adjusts not available</b>													
<b>Cable / Connector</b>													
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland										
Connector - Axial M8 4 pin IP67		J											
<b>OPTIONS</b>													
<b>Housing</b>													
Front Flange		N	<b>Option 1</b>										
<b>Body Clamp</b>													
Body Clamps (1 pair)		P	<b>Option 2</b>										
<b>Spring Loaded</b>													
Spring Loaded (extended)		R	<b>Option 3</b>										
<b>Plunger End Fitting</b>													
Dome End		T	<b>Option 4</b>										
<b>Plunger (Armature) Guide</b>													
Free Plunger (no inner guide bearing)	Not available with option R or T	V	<b>Option 5</b>										
<b>Tighter Linearity</b>													
± 0.1% Linearity from 10mm stroke only		Z650	<b>Zsuffix</b>										