

Part Number Coding

RIPS® SERIES P502			P502	Travel	Electrical Interface	Sealed Adjusters	Conn / Cable and	Option 1	Option 2
Small Angle Industrial Rotary Sensor									
Travel									
degrees rotation	5° to 20°	Value							
Electrical Interface Options									
Input			Output						
+ 5V dc nom.± 0.5V			0.5 to 4.5V dc ratiometric	A					
24V dc nom. +9-28V			0.5-4.5V dc	G					
±15V dc nom. ±9-28V			±5V dc	B					
24V dc nom. +13-28V			0.5 to 9.5V dc	C					
± 15V dc nom. ±13.5-28V			±10 V dc	D					
24V dc nom. +18-28V			4 to 20mA (2 wire)	E					
24V dc nom. +13-28V			4 to 20mA (3 wire sink)	F					
24V dc nom. +13-28V			4 to 20mA (3 wire source)	H					
Calibration Adjusters									
Trim Pots Accessible			Sealed Trim Pots						
			Blank						
			Y						
Connector / Cable									
Connector - Axial IP65			Hirschmann GD series						
			J						
Cable - Axial Gland IP67			Please specify cable length in cm.			Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland		
Cable - Axial Short Gland IP67			Please specify cable length in cm.			Mxx	Note: restricted cable pull strength		
OPTIONS									
Spring Return									
Fitted									
			N						
Housing									
Flanged			Standard option no code			Blank			
Servo Mount						P			