

Intrinsically Safe - Gas LIPS® SERIES X103		Part Number Coding										
		X103	Travel	A	Sealed Adjusters	Conn / Cable	Option 1	Option 2	Option 3	Option 4	Option 5	Z code
<b>Short Stroke Position Sensor</b>												
<b>Travel</b>												
mm of stroke	Value											
<b>Electrical Interface Options</b>												
<b>Input</b>		<b>Output</b>										
+ 5 V dc	See below	A										
<b>Calibration Adjusters</b>												
Trim Pots Accessible	Blank											
Sealed Trim Pots	Y											
<b>Connector / Cable</b>												
Connector - Axial IP65	Hirschmann GD series	J										
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of cable with an axial cable gland									
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx	Note: restricted cable pull strength									
<b>OPTIONS</b>												
<b>Housing</b>												
Front Flange	N				Option 1							
<b>Body Clamp</b>												
Body Clamps (1 pair)	P				Option 2							
<b>Spring Return</b>												
Spring Return	R				Option 3							
<b>Target End Fitting</b>												
Bull Nose	T				Option 4							
<b>Target (Armature) Guide</b>												
Free target (no inner guide bearing)	Not available with option R or T	V			Option 5							
<b>Calibration (output from galvanic barrier)</b>												
0.5 to 9.5 volts	Z010											
4 to 20 mA	Z420											