


Intrinsically Safe - Gas LIPS® SERIES X106		Part Number Coding									
		X106	Travel	A	Sealed Adjusters	Conn / Cable	N	Option 2	R	Option 4	Z code
Internally Mounted Cylinder Sensor											
Travel											
mm of stroke		Value									
Electrical Interface Options											
Input		Output									
+ 5 V dc		See below		A							
Calibration Adjusters											
Trim Pots Accessible		Blank									
Sealed Trim Pots		Y									
Connector / Cable											
Connector - Axial IP65		Hirschmann GD series		J							
Connector - Radial IP67/68											
Cable - Axial Gland IP67		Please specify cable length in cm.		Lxx eg. L2000 specifies 20 metres of cable with an axial cable gland							
Cable - Axial Short Gland IP67		Please specify cable length in cm.		Mxx Note: restricted cable pull strength							
OPTIONS											
Internal Housing Size											
20 mm Diameter		Standard Fit		N							
Electronics Housing											
Flanged		T		Option 2							
M18 Thread		P									
Target Tube											
Stainless Steel 7.7 mm		Standard Fit		R							
Flange Style and Position Please select one.											
None		U		Option 4							
P&G		Vxx		← Distance to back of flange in mm							
Tempo		Wxx									
PH		Xxx									
See Drawing TG24-11 for flange details											
Calibration (output from galvanic barrier)											
0.5 to 9.5 volts		Z010									
4 to 20 mA		Z420									