


Intrinsically Safe - Gas		Part Number Coding									
<b>LIPS® SERIES X106</b>		<b>X106</b>	Travel	A	Sealed Adjusters	Conn / Cable and	N	Option 1	R	Option 2	Z000
<b>Internally Mounted Cylinder Sensor</b>											
<b>Travel</b>											
mm of stroke	Value										
<b>Electrical Interface Options</b>											
<b>Input</b>	<b>Output</b>										
+ 5 V dc	See below	A									
<b>Calibration Adjusters</b>											
Trim Pots Accessible	Blank										
Sealed Trim Pots	Y										
<b>Connector / Cable</b>											
Connector - Axial IP65	Hirschmann GD series	J									
Connector - Radial IP67/68											
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx eg. L2000 specifies 20 metres of cable with an axial cable gland									
Cable - Axial Short Gland IP67	Please specify cable length in cm.	Mxx Note: restricted cable pull strength									
<b>OPTIONS</b>											
<b>Internal Housing Size</b>		Standard Fit									
20 mm Diameter	Standard Fit	N									
<b>Electronics Housing</b>		Option 1									
Flanged	T										
M18 Thread	P										
<b>Target Tube</b>		Standard Fit									
Stainless Steel 7.7 mm	Standard Fit	R									
<b>Flange Style and Position</b> Please select one.		Option 2									
None	U										
P&G	Vxx										
Tempo	Wxx										
PH	Xxx										
Please specify flange position xx from Target Tube end in mm. eg. W17.5 specifies a Tempo style flange fitted 17.5 mm from the front face											
See Drawing TG24-11 for flange details											



Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005 sheet for Output options.