

ELECTRICAL OPTIONS/ SPECIFICATIONS

OUTPUT **SUPPLY**
 CODE 'A' 0.5 TO 4.5V RATIO METRIC 5V
 SUPPLY CURRENT 12mA TYP. 20mA MAX.

CABLE LENGTH, OPTION 'Lxx', ORDERED IN cm, 50cm
 STANDARD OR AS REQUIRED.

3-CORE SCREENED: 0.2mm², 4mm PUR JACKET

CABLE/CONNECTOR CONNECTIONS;
 3 CORE


RED +Ve
 BLACK 0V
 WHITE OUTPUT
 SCREEN BODY

RANGE OF DISPLACEMENT FROM 30° TO 140°,
 IN INCREMENTS OF 1°.

BODY MATERIAL:- ALUMINIUM ALLOY.

H	REDRAWN	PDM
I	BOSS Ø10.00 ADDED	PDM
J	ADDITIONAL DIMS/VIEWS ADDED.	PDM

DRAWINGS NOT TO BE CHANGED WITHOUT REFERENCE TO THE CHANGE PROCEDURE.
 CHANGES TO PARTS USED IN INTRINSICALLY SAFE PRODUCT MUST BE APPROVED
 BY THE AUTHORISED PERSON
 THIS IS AN UNCONTROLLED PRINT AND WILL NOT BE UPDATED.



H	19/10/06		CHECKED BY	X	±0.4
I	15/01/09		RDS	X.X	±0.2
J	06/07/11			X.XX	±0.1
				DIMS	mm
DESCRIPTION					
P501 RIPS MINIATURE ROTARY SENSOR					
SCALE			DRAWING NUMBER		
10mm			P501-11		
			REV J		
			SHEET 1 OF 1		