


Intrinsically Safe - Dust LIPS® SERIES H130		Part Number Coding							
		H130	Travel	A	Y	Conn / Cable and Length	Option 1	Option 2	Z000
Long Stroke In-Cylinder Linear Position Sensor									
Travel									
mm of stroke	400-1485 mm	Value							
Electrical Interface Options									
Input	Output								
+ 5 V dc	See below	A							
Calibration Adjusters		Standard Fit							
Sealed Trim Pots		Y							
Connector / Cable									
Connector - Axial IP67		J							
3 Core Cable Axial Gland IP67	Please specify cable length in cm.	Lxx							
		eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland							
5 Core Cable Axial Gland IP67	Please specify cable length in cm.	LQxx							
		eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland							
3 core cable with Short IP67 Axial Cabl	Please specify cable length in cm.	Mxx							
		Note: restricted cable pull strength. eg. M2000							
5 core cable with Short IP67 Axial Cabl	Please specify cable length in cm.	MQxx							
		Note: restricted cable pull strength. eg. MQ2000							
OPTIONS									
Housing Size	Please select one.	Option 1							
M20		N							
M18		T							
3/4 UNF		P							
See P100-15 Drawing for Mating Thread Details									
Flange Style and Position		Option 2							
Please select one of the following:									
'Circlip Fit' style		Vx							
'Screw Fit' style		Wx							
		Please specify flange position x from Target Tube end in mm.							
		eg. V17.5 specifies a 'Circlip Fit' style flange fitted 17.5 mm from the front face							



Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See G005 sheet for Output options.