

Intrinsically Safe - Gas RIPS® SERIES X505		Part Number Coding																																														
		X505	Travel	A	Cable Length	Option 1	Z000																																									
Slim-line Rotary Sensor																																																
<table border="1"> <tr> <td colspan="7">Travel</td> </tr> <tr> <td>degrees rotation</td> <td>15° to 160°</td> <td colspan="5">Value</td> </tr> </table>							Travel							degrees rotation	15° to 160°	Value																																
Travel																																																
degrees rotation	15° to 160°	Value																																														
<table border="1"> <tr> <td colspan="7">Electrical Interface Options</td> </tr> <tr> <td colspan="3">Input</td> <td colspan="4">Output</td> </tr> <tr> <td>+ 5 V dc</td> <td>See below</td> <td colspan="5">A</td> </tr> </table>							Electrical Interface Options							Input			Output				+ 5 V dc	See below	A																									
Electrical Interface Options																																																
Input			Output																																													
+ 5 V dc	See below	A																																														
<table border="1"> <tr> <td colspan="7">Cable / Connector</td> </tr> <tr> <td>Cable - Axial Gland IP67</td> <td>Please specify cable length in cm.</td> <td colspan="5">Lxx eg. L2000 specifies 20 metres of cable.</td> </tr> <tr> <td>Connector - Axial M8 4 pin IP67</td> <td colspan="6">J</td> </tr> </table>							Cable / Connector							Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx eg. L2000 specifies 20 metres of cable.					Connector - Axial M8 4 pin IP67	J																										
Cable / Connector																																																
Cable - Axial Gland IP67	Please specify cable length in cm.	Lxx eg. L2000 specifies 20 metres of cable.																																														
Connector - Axial M8 4 pin IP67	J																																															
<table border="1"> <tr> <td colspan="7">OPTIONS</td> </tr> <tr> <td colspan="7">Housing</td> </tr> <tr> <td>Flanged</td> <td>Standard option no code</td> <td colspan="5">Blank</td> </tr> <tr> <td>Servo Mount</td> <td colspan="6">P</td> </tr> <tr> <td colspan="7">Tighter Linearity</td> </tr> <tr> <td>± 0.1% Linearity</td> <td>up to 100°</td> <td colspan="5">Z650</td> </tr> </table>							OPTIONS							Housing							Flanged	Standard option no code	Blank					Servo Mount	P						Tighter Linearity							± 0.1% Linearity	up to 100°	Z650				
OPTIONS																																																
Housing																																																
Flanged	Standard option no code	Blank																																														
Servo Mount	P																																															
Tighter Linearity																																																
± 0.1% Linearity	up to 100°	Z650																																														

Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005